air outlet and reading light are provided for each seat and a cold air outlet and reading light for each upper bunk. The oxygen mask-to-regulator tubes for the aft inboard seats are 6 feet long for use in the upper bunks. A warm air outlet, located in the sidewall at floor level, is provided for each double seat. A walk around oxygen bottle and recharger station and two first aid kits are located at the forward end of this section. An ash tray is provided for each seat, housed in the seat arm rest.

FLIGHT COMPARTMENT AFT SECTION

The aft section of the flight compartment extends from Station 475 to the pressure bulkhead at Station 550. The right side is occupied by the main electrical junction boxes and wire trough and the left side contains the galley and toilet area.

The galley contains provisions for ovens, heated liquid containers, dry-ice refrigerator, wall-type can opener, cup dispenser, storage space for flight meals and miscellaneous articles and a waste container. Located overhead is an air exhaust outlet for removing food odors and a light for illuminating the face of the galley.

The toilet compartment is located aft of the galley and separated from the center aisle by a curtain. This compartment includes the toilet, paper holder, ash tray, a portable oxygen-bottle recharger and the waste water tank. The toilet bucket is removable for emptying and cleaning and will have a sealed lid to prevent spillage. Disposable containers may be used, if available.

The urinal is aft of the toilet and separated from it so that both may be used simultaneously. It is also separated from the center aisle by a curtain. The urinal drains into a separate tank which may be emptied from a service panel at ground level. The shut-off valve is located above the floor in the flight compartment to prevent freezing of the line in flight. Air from both the urinal and toilet areas is vented overboard.

The wash basin is located adjacent to the toilet compartment and is accessible from the center aisle. Adjacent to the basic are a towel dispenser, mirror, soap dispenser, waste paper bin lined with a disposable water-resistant paper bag, and a miscellaneous stowage cabinet. Also provided are a first aid kit and fire extinguisher and an emergency light for the exit in the pressure bulkhead.

A 15-gallon stainless steel water tank is installed overhead for supplying the wash basin. The tank is filled from a ground level service panel. A combination overflow and vent line routed to the 16 gallon waste tank prevents bursting tank and lines.